

MAGNUM® MP212 Slabjack Pier

4 Tons Allowable Capacity in Compression


High-Strength 1.75" Diameter, 0.12" Wall, Round-Shaft

Slabjack Pier with Male-Female Slip Connectors



Description

Magnum® MP212 slabjack piers have a structural capacity in compression of 8 tons ultimate and 4 tons allowable. Slabjack piers do not have tensile capacity unless the sections are welded together or a reinforcing steel bar and grout is placed in the pile casing. Sections couple together with male-female slip connectors. High strength steel offers increased buckling resistance compared to others. A friction reduction collar can be added to the pile to increase penetration depth. Sections are available in bare steel, epoxy powder coated, and galvanized. Galvanized coating extends average life expectancy to over 100 years even in highly corrosive environments. Custom lengths are available upon request. See Magnum® Technical Manual for additional information.



SPECIFICATIONS	
Shaft	HSS 1.75" x 0.12" wall ASTM A513 Grade 65 ksi, or Equivalent
I	New= 0.21 in ⁴
A _g	New= 0.61 in ²
S	New= 0.23 in ³
Coupling	Inner 0.12" Sleeve
Coating	Hot-Dip Galvanized (G), Bare Steel (NG), or Epoxy Powder Coated (EP)
Standard Ram	RAM 3.14 in ² Piston Area, 7,500 Maximum P.S.I. (4,000 Max. P.S.I. Installation Pressure)
STRUCTURAL CAPACITY IN COMPRESSION*	
8 Tons	Ultimate
4 Tons	Allowable
CAPACITY FROM LOAD TEST**	
6 Tons	Maximum Test Load
4 Tons	Allowable from Test (F.S.=1.5)

*Note 1: Structural capacity is based on buckling strength of shaft in firm soils with pinned head conditions without corrosion (temporary short-term applications). Push piers shall be installed to appropriate depth into suitable bearing stratum as determined by geotechnical engineer or local practice. For tension capacity, push pier sections must be welded together or a reinforcing steel bar and grout must be placed in the pile.

**Note 2: Push pier capacity is determined by load test using Magnum installation rams or lifting kit. All push piers shall be load tested to 1.5 times the desired working load. Test load is limited by maximum safe operating ram pressure or buckling capacity of shaft, whichever is less.

Magnum Piering, Inc.

6082 Schumacher Park Dr.

West Chester, OH 45069

800-822-7437

www.magnumpiering.com

All Magnum Products Made in U.S.A.

U.S. Patents 6,058,662 and 5,234,287; Other Patents Pending.