



isclaimer

By the title of this presentation, some of our competitor's in the deep foundation industry might say "see helical piles don't work". That is <u>not</u> the subject of this presentation. With the variety of subsurface profiles, diverse geologic conditions, and a myriad of structures to be supported, the engineer and contractor need as many resources in their tool belt as possible. Helical piles and helical anchors represent one of those tools which, when used correctly, perform effectively. Like all piles and ground reinforcing elements, helical piles and helical anchors used incorrectly can have less than favorable results. Several case histories with less than favorable results are presented here so the audience can learn the correct application of helical piles and helical anchors.
































































































Buckled Underpinning in New York



- Helical piles were installed to reduce settlement during conventional concrete underpinning
- Footing rotated, piles buckled, and building settled severely
- Photo shows supplemental raker bracing system installed with deadmen after settlement



- Photo shows buckled pile and bracket system
- Helical piles were 1-3/4" square shaft with reinforcing sleeves
- All piles were installed along the outside of the building
- This and a similar failure were catalysts to a nearly 2 yr moratorium on helical piles in NYC




Potential Cause of Failure

• Failed to brace the tops of piles


Per IBC2006: 1807.2.4 Pile or Pier Stability


- All piles shall be braced for lateral stability
- Three or more piles per cap is considered braced
- Piles staggered under a wall are considered braced
- Otherwise provide engineered means of lateral bracing







- Another solution is to brace to wall laterally at the top of piles as in this photo.
- Square plates along the base of the wall are concrete anchors extending into the building slab.
- All piles were designed to withstand buckling while excavation was open.













Potential Causes of Failure


- Soil nails lacked continuous bonding
- Soil nail spacing too far apart
- Soil nail length too short
- Bearing capacity failure
- Insufficient lapping of reinforcing steel
- Poor drainage























- Approximately 140 helical piles installed to support several 5story apartment buildings
- Design load of helical piles = 90 to 130 kip
- Immediately after construction, several of the buildings exhibited settlement on the order of 4"
- Three of the buildings had to be demolished and re-built. The others were repaired by underpinning.





Potential Causes of Failure

- Non-conforming helix invalidates capacity to torque readings
- Insufficient bearing area; relied on torque alone and did not check theoretical bearing capacity
- Over-reliance on load tests











 Example Frame Scaffolding (Note: This is not the actual scaffold that collapsed. Due to confidentiality, actual scaffold cannot be shown.)

- Approximately 4-story tall, temporary, stand-alone scaffold towers were erected to construct an elevated concrete walkway
- Each scaffold tower was supported on 8 helical piles
- During concrete placement, scaffold gave-way killing one worker and injuring 18 others

Potential Causes of Failure

- Structural issues associated with scaffold design
- Lack of lateral stability
- No lateral capacity specification for the piles
- Square-shaft helical piles have negligible lateral capacity





Collapse During Foundation Repair





- An addition was being constructed on the back of this home
- The existing back wall experienced settlement
- A foundation repair contractor was called out to install several piles along the back wall

