

MAGNUM® MP1039-3 Pin Bracket


Allowable Capacity 25 Tons




3" x 8" x 1/2" Plate and 3.13" I.D. Collar

Fits MH313B, MH313BR, MH325, MH325BR Helical Piles and MP313, MP325 Steel Push Piers

Description: The MAGNUM® Pin bracket consists of a collar tube with (3) 3/4" threaded bolt holes for connection to MAGNUM® helical piles and push piers and steel plate for welded attachment to existing steel. MAGNUM® products are manufactured in the USA according to our ISO 9001 approved quality program. MAGNUM® brackets are designed in accordance with ICC-AC308, IBC, ACI, and AISC codes. Design and detailing of the connection to the structure varies by project and is the responsibility of the registered design professional including weld to existing steel, maximum concrete span, pier spacing, concrete shear, and concrete bearing.

Specifications	
Collar Tube	0.37 in. x 3.13 in. I.D. ASTM A513, Fy = 65 ksi or Better
Configuration	3" x 8" x 1/2" Plate Weld Flange
Pile Connection	(1, 2, or 3) 3/4" SAE J429 Grade 8 Zinc Coated to ASTM B695/F1941
Surface Coating	Bare Steel (NG) or Standard MAGNUM® Blue Paint (P)
Compatibility	MH313B, MH313BR, MH325B, MH325BR(-6), MP313 & MP325



Connection Type	Ultimate Capacity*	Allowable Capacity*
 Single Bolted	10 Tons / 18 Tons	5 Tons / 9 Tons
 Double Bolted	17 Tons / 35 Tons	8 Tons / 18 Tons
 Triple Bolted	28 Tons / 50 Tons	14 Tons / 25 Tons

*Bracket connection to pile consists of field threaded blind bolts as described in Section 7-13 of AISC Code. Capacities shown are based on IAS accredited laboratory testing of MAGNUM® products.

Installation Notes: Prepare the existing foundation. For steel push pier applications, prepare the structural steel for welding, then attach the bracket and MAGNUM® ram. Install the push pier to the required pressure and load test. For helical pile applications, post-hole excavate the pile location so the helix bearing plates fit below the existing foundation and the shaft is as close as possible to the face of the foundation. Install the helical pile to the correct depth and torque. Prepare the structural steel for welding, then mount the bracket and install the sleeve. In both cases, lift the structure as needed using either a MAGNUM® ram or lifting fixture. Drill holes and bolt the bracket to the pile.



U.S. Patents 5,234,287, 4,708,528, 5,123,209

MAGNUM®
PIERING
designed to support

156 Circle Freeway Dr.
Cincinnati, OH. 45246
800-822-7437
www.MagnumPiering.com